Safety Data Sheet



Elgamatic 103 **GMAW Un-alloyed**

1. Product and Company identifications

Product name:	Elgamatic 103
Application:	Arc welding
Classification(s):	EN 440 G4Si1
	AWS A5.18 ER 70S-2
Supplier:	Elga AB
Address:	Box 277, SE-433 25 Partille, Sweden
Telephone:	+46 31 7264600
Fax:	+46 31 7264700
Internet:	www.elgawelding.com

2. Wire composition

Ingredient	Weight%	Cas No	H-symbol	R-phrases	
Carbon	0,065	133-86-4	n/a	n/a	
Silicon	0,90	7440-21-3	n/a	n/a	
Manganese	1,65	7439-96-5	n/a	n/a	
Chromium	0,03	7440-47-3	n/a	n/a	
Nickel	0,015	7440-02-0	n/a	R40-43	
Molybdenium	0,004	7439-98-7	n/a	n/a	
Copper	0,009	7440-50-8	n/a	n/a	

Xn=Harmful, R40=Possible risks of irreversible effects, R43=May cause sensitisation by skin contact.

3. Hazards identification

This product contains nickel that is classified as both a potential skin allergen and an element with limited evidence of a carcinogenic effect according to EC Directive 67/548/EEC. Nickel in the form of this product does not contribute to a hazard classification of the product.

When the product is used in the welding process the most important hazards are; Heat: spatter, hot metal and slag can burn skin and cause fire. Radiation: arc rays can injure eyes and burn skin. Electric shock: can kill. Dust. can cause irritation to eyes and lungs. Fume: overexposure to fumes and gases can be dangerous to health.

4. First aid measures

Inhalation: if breathing is difficult, provide fresh air and call a doctor. Burns: for skin burns from radiation, see doctor. Eye injuries: for radiation burns (arc flash), see doctor; for dust irritation rinse eyes with eyewash solution

5. Fire fighting measures

No specific requirements applicable.

6. Accidental release measures

Personal: see section 8. Environmental precautions: see section 13. Methods for cleaning up: see section 13.

7. Handling and storage

No specific safety precautions necessary in the form supplied.

8. Exposure controls/personal protection

Engineering measures: General ventilation and local fume extraction must be adequate to keep fume concentrations within safe limits for both the welder and others.

The long-term exposure limit for Cr(VI) is 0.05 mg/m³.

Personal protection: Use respiratory protective equipment when welding in a confined space. Wear protective clothing and eye protection appropriate to arc welding. Avoid touching live electrical parts.

Part no:	9523- XXXX		
Date:	2003-03-17		

9. Physical and chemical properties

Physical state:	Solid
Odour:	Odourless
Colour:	Copper coated
Form:	Rod

10. Stability and reactivity

Conditions to avoid: n/a

Hazardous decomposition products: welding fumes and gases. Additional fume may arise from different base materials, coatings and contaminants on the base material.

Fume analysis: wt %

i anto ana	yolo. III /0					
Fe	Mn	Ni	Cr	Cu	Pb	F
50	5-10	<0.1	<0.1	1	<0.1	-

Refer to applicable national exposure limits for welding fume and its compunds.

11. Toxicological information

No effects in the form supplied. When welding, fumes and gases generated can be dangerous to health. Short-term overexposure can cause dizziness, nausea and irritation of the nose, throat or eyes.

Long- term overexposure may effect the lungs.

Overexposure to manganese may affect the nervous system.

Certain chromium and nickel compounds, like Cr(VI) are suspected of being cancercausing agents.

12. Ecological information

The welding process can effect the environment if fume is released directly into the atmosphere.

Cr(VI) is suspected of being very toxic to aquatic organisms and may cause long-term adverse effects in the aquatic environment. Residues from welding consumables could degrade and accumulate into soils and ground water.

13. Disposal considerations

Dispose of any product, residue or packing material according to national and local regulations. Use recycling procedures if available. Spent fume extraction filters shall be disposed of as dangerous waste.

14. Transport information

No special precautions apply.

15. Regulatory information

Local laws and regulations should be carefully observed.

In case of insufficient ventilation wear suitable respiratory equipment. 16. Other information

Elga requests the users of this product to read this Safety Data Sheet carefully and become aware of hazards implied and the Safety information. The customer should provide this Safety Data Sheet to any person involved in its use or further distribution.

This Safety Data Sheet complies with the EC-directive 93/112 and ISO 94-11014-1 and is based on present knowledge and regulations. This information is to be considered as a general guidance.