



SILICONI COMMERCIALE SpA

CHEMICAL PRODUCTS FOR INDUSTRY
Via Francia, 4 - 36053 GAMBELLARA (VI) ITALY
TEL.0039 444 649766 - FAX 440018
www.siliconicommerciale.it



ANTITEK

SILICONE FREE ANTISPATTER SPRAY FOR WELDING

CHEMICAL BASE

BASE : Mixed Synthetic oil.
PROPELLENT : Mixed gas, denaturate, not toxic, ecological.
ASPECT : transparent liquid
VISCOSITY at 25°C : 20-50 cST
ODOUR : odourless

MAIN CHARACTERISTICS

- NOT INFLAMMABLE
- NOT TOXIC
- NOT INJURIOUS
- CFC FREE
- SILICONE FREE

Thank to its characteristics ANTITEK is the new generation of the ecological antispatters spray; in fact it is **biodegradable** and not toxic or injurious for the user's health, and it is not inflammable.

APPLICATION

ANTITEK is used to prevent the adhesion of the drosses and of the drops on the welding and on the cut of the metals.

This product permits the superficial successive treatments (painting, galvanizations, chromium-plating) because it doesn't contain silicone

DIRECTIONS FOR USE

Shake well before use.

Spray the product around the mouth of the torch and over the metal to weld or to cut.

Spray it at 25-30 cm distance, and don't spray to much.

MANUFACTURE

Cod. 106K aerosol 400/500 ml

Box 25 pieces.

The manufacturer cannot be held responsible in case of damages caused by correct or incorrect use of the product.