SILICONI COMMERCIALE SPA Via Francia 4 36053 Gambellara (VICENZA) ITALY TEL +39.0444.649766 info@siliconi.it www.siliconi.it

TECHNICAL DATA SHEET



ANTIRUGGINE

ANTIRUST PROTECTIVE FOR METALS

CHEMICAL BASE

 BASE:
 mixture of oils and antirust additives.

 ASPECT:
 amber liquid

 RESISTANCE TO TEMPERATURES:
 130 °C

 VISCOSITY AT 25 °C
 : 20-50 cSt

 DILUBILITY
 : in solvent

 ODOUR
 : Characteristics

 SELF LIFE
 :24 months

 SILICONE FREE
 :24 months

USE

Antitrust Protective for: moulds, iron pieces.

APPLICATIONS

It is used as a protective for machines, moulds, and different tools or objects subjected to rust and that have to be stocked for long periods.

ADVANTAGES:

High protection against rust

It ia a good "dewatering"; It eliminates water and humidity for the surfaces treated.

This product pemits to stock moulds, finished pieces, pieces partially worked, protecting them from rust even in humid places or in places subjected to atmospherical agents. It covers hermetically thin film of protective fluid the surfaces.

OPERATING INSTRUCTIONS:

First of all it is very important to clean very well the metal surfaces to be treated with a specific metal cleaner such us METACLEAN. Spray it at 20 cm distance let the product act and the air polimerized. It makes a oil film that it is easy to remove with normal solvents.

MANUFACTURE

cod. 10810/05 spray aerosol ml 500 box: 25 aerosols.