SILICONI COMMERCIALE SPA

Via Francia 4 36053 Gambellara (VICENZA) ITALY TEL +39.0444.649766 info@siliconi.it

www.siliconi.it

TECHNICAL DATA SHEET



INOXSIL

STAINLESS STEEL SPRAY

CHEMICAL BASE

Principale: Stainless steel paint in sinthetic vehicle. Propellent: Denaturate and odourless hydrocarbure.

Colour : Metallic Solvents: chlorides Dryness time: 5'

Film Thickness: 25-30 micron Temperaure resistance: high

APPLICATIONS

INOXSIL is an stainless steel spray product.

It forms a film which restores and protects all stainless steel surfaces.

It can be overpainted or left as final protection.

It has a good covering power and repristinate all stainless steel surfaces.

OPERATING-INSTRUCTIONS

Clean and degrease the parts to treat. Shake continually the spray until the little ball is free to move and during the application continue occasionally to shake the product to keep it homogeneus. Spray at 25 cm distance. After the use overturn the aerosol and spray the product few seconds to dodge the obstruction of the valve.

MANUFACTURE

cod. 11210/04 spray aerosol ml 400 box: 12 aerosols.

The information and recommendations contained in this document is offered in good faith based on our current knowledge and belief accurate at the date of publication. Nothing herein is to be considered as a warranty, express or otherwise. In all cases, it is the responsability of the user to determine the applicability of such information or the suitability of any products for their own particular purpose with local legislation and for obtaining the necessary certifications and authorisations. Siliconi Commerciale's sole warranty is that the products will meet its sales specification. The manufacturer cannot be held responsable in case of damages caused by incorrect use of the product.

(a) indicates a Registered TradeMarks of Siliconi Commerciale. All Rights Reserved.