



SILICONI COMMERCIALE SpA

CHEMICAL PRODUCTS FOR INDUSTRY

Via Francia, 4 - 36053 GAMBELLARA (VI) ITALY

TEL. 0039 0444 649766 - FAX 440018

www.siliconicommerciale.it



TECNICAL DATA SHEET

MOLISIL

ANTIADHESIVE SPRAY WITH MoS₂

CHEMICAL BASE

BASE : Bisulfure of molybdenum in synthetic vehicle

PROPELLENT : Denaturate and odourless hydrocarbure

APPAREANCE: Dry grey film

TEMPERATURE RESISTANCE: 700°C (the bisulfure of molybdenum)

SILICONE FREE

CFC FREE

APPLICATION

MOLISIL is used as ANTISPATTER to protect the nozzle of the torch against the drops adhesion. It is a very good antispatter because it contains MoS₂ and it resists much more than a normal antispatter oil based.

MOLISIL it can be used also as LUBRICANT to lubricate the mechanical parts in movement preventing the friction and reducing the strain. It is used to rubricate under high temperatures.

DIRECTION FOR USE

Clean and degrease the parts to treat. Shake continually the spray until the little ball is free to move and during the application continue to shake the product to keep it homogeneous. Spray it from a 25 cm distance. After the use overturn the aerosol and spray the product few seconds to dodge the obstruction of the valve.

MANUFACTURE

COD. 11610/05 SPRAY AEROSOL ml 500

Box 25 AEROSOLS

The manufacturer cannot be held responsible in case of damages caused by correct or incorrect use of the product.