

### AGCW-28P Excel Outfit Light Duty AGA<sup>®</sup> X11 Style

#### Capacity

Cutting up to 4" (100mm), Welding up to 1/2" (12mm) steel.

#### Packing

Strong and attractive PP case, which easy for carrying and storage.

#### Features

- \* Torch handle w/two stainless steel needle valves for fast, accurate flame adjustment.
- \* Torch handle front piece & body of forged brass made for durability
- \* Torch handle bakelite coated good for heat resistance & comfort.
- \* Torch handle w/two separate gas tubes for safety.
- \* Torch handle w/quick connector.
- \* Cutting attachment center brass press lever can 180° for easy cutting & convenient use.
- \* Cutting attachment w/teflon packing for quick hand-tight seal, leak free & durability.
- \* Cutting attachment mixer inside the body portion for operator safety.
- \* Cutting attachment head & body in forged brass for longer life.
- \* Cutting attachment medium pressure design resists backfire.
- \* Chrome copper welding tip for long lasting & beauty.
- \* Flat seat cutting tips for longer life.
- \* Swaged copper welding tips for best flame characteristics and can individualize mixer.
- \* Hose connections is BSP 1/4". Other thread sizes are available.

#### Application

Precise welding, brazing, soldering, hard facing, heat/treating, and priming, straightening, descaling and scarfing, gouging, flame cleaning, rivet washing and cutting.



#### Complete Outfit Contents

Contents	Torch Handle	Cutting Attachment	Check Valve	Quick Connector	Tips (Size)		Accessories
					Welding	Cutting	
Model	AG-281	AG-282	optional	AG-283	AGA-W (1, 2, 3, 4, 5 & 6)	HA211 Type AGA-C (1, 2, 3, 4)	Wrench, 3 Teflon packing, Twin wheel circle guide and Tip cleaners.

Note: Outlet connection can be supplied to suit country.

Inlet connection can be supplied to suit country & switched to side entry or bottom center entry.

